



PILOSIO



SECUR-BLIND

INNOVATIVE CONSTRUCTION SITE PROTECTION

It is a construction site protection created by Pilosio: safe and easy to use, it can be hooked onto scaffolding or a tubular structure, it replaces construction site fencing and greatly improves the aesthetics of the construction site. It is a clever system that uses components that are light and quick to assemble, and elements designed specifically to meet the needs of each client.

Thanks to its nice aesthetics, it greatly improves the visual impact of the construction site especially in historical centers. It is possible to obtain hermetic or fireproof and soundproof protection with components provided with gasket and insulating slabs. On request, panels of any size can be made according to the specific needs of the construction site.

SECUR-BLIND consists of panels inserted inside aluminum rails fastened in a quick and easy manner with a pincer clamp on the 48.3 mm pipes of the scaffold or any other structure. Fixed and variable angle bars and access gates complete the system.

It is a tailor-made protection that is extremely easy to assemble.





INNOVATION

The future in construction site protection



MODULARITY

It is re-adaptable and can fit any construction site need



FLEXIBILITY

I can be used with any



SAFETY

It provides greater type of scaffolding and anti-intruder protection than on any existing structure construction site fencing



SIMPLICITY

Ease and fast assembly and disassembly without tools



DUST IMPERMEABILITY

High protection from dust and waste from site processing



HERMETIC, **SOUND-ABSORBING** AND FIREPROOF

Hermetic panels with fireproof and soundproof PL slab are available



CUSTOMIZATION

On request, it is possible to manufacture panels of different sizes

TECHNICAL DATA AND COMPONENTS

- Galvanized steel panels in solid sheet or with grid, hermetic, fireproof and soundproof panels.
- Panel dimensions: 50x100 cm, 50x150 cm, 50x180 cm, 50x200 cm, 50x250 cm
- H=200 cm aluminum uprights and hermetic uprights
- Galvanized steel foot for each upright to lock the panels
- H=49 cm external and variable galvanized steel corner
- L=100 H=200 single leaf access gate or L=180 H=200 double leaf access gate
- Galvanized pincer clamp
- 012 mm galvanized flexible pin
- On request, panels in different colors and sizes



APPLICATIONS

- Construction site perimeter fencing and protection
- Shielding for environmental protection from slags produced by special processing
- Building, renovation and industrial maintenance construction sites







Pilosio Srl - Via E. Fermi, 45 - 33010 Feletto Umberto - Tavagnacco (UD) - Italy Tel. +39 0432 435311 - www.pilosio.com - info@pilosio.com